


## Specifications for Selected ULDs

		ULD Common Designation	Max External Dimensions L x W x H (in/cm)	Internal Cubic Capacity (ft³/m³)	Maximum Gross Weight (lb/kg)	Weight Tare (approx) (lb/kg)
		A-2	88 x 125 x 82 in 223 x 317.5 x 208 cm	440 ft <sup>3</sup> 12.5 m <sup>3</sup>	13,300 lb 6,033 kg	476 lb 216 kg
		AM	96 x 125 x 82 in 243.84 x 317.5 x 208.28 cm	623 ft³ 17.6 m³	15,000 lb 6,803 kg	630 lb 286 kg
		PB (463L)	88 x 108 x 82 in 244 x 274.3 x 208.28 cm	380 ft³ 10.7 m³	10,000 lb 4,535 kg	185 lb 84 kg
	<b>T</b>	AKE	60.4 x 79.0 x 64.0 in 153.4 x 200.6 x 162.56 cm	153 ft³ 4.3 m³	3,500 lb 1,588 kg	191 lb 87 kg
		PKC	61.5 x 60.4 x 71.0 in 156.2 x 153.4 x 180.34 cm	153 ft³ 4.3 m³	3,500 lb 1,588 kg	154 lb 70 kg

#### Cross Section Showing Main Deck and Lower Compartment




### Typical Main Deck Cargo Layout




#### Cargo Layout Legend







Aft Cargo Compartment



(1) 61.5 in x 60.4 in x 71.0 in Pallets at 153 cu. ft.

#### Typical Lower Lobe Deck Cargo Layout



# 737-800BCF Specifications

Maximum Revenue Payload	52,800 lb	23,950 kg	Maximum Design Range	2,609 nmi	4,830 km
Main Cargo Compartment	4,993 ft <sup>3</sup>	141.4 m³	Maximum Gross Takeoff Weight	174,000 lb	79,000 kg
Lower Forward/Aft Compartment (Bulk)	1,543 ft <sup>3</sup>	43.7 m <sup>3</sup>	Maximum Gross Landing Weight	146,300 lb	66,350 kg

Cargo data based on Weight & Balance Manual

